

MULTI-TEC + B4 10W30

MULTI-TEC + B4 10W30 is an advanced motor oil on synthetic base, especially designed for the lubrication of all 4-stroke gasoline and diesel engines.

MULTI-TEC + B4 10W30 meets the following specifications:

- API SL/CF
- ACEA A3/B3/B4-04
- MB 229.1

ADVANTAGES :

- High fluidity at low temperature due to the use of components of very high quality.
- Very strong resistance against oxidation.
- Very stable viscosity at high temperature.
- Very high resistance against wear, corrosion and foaming.
- Lower fuel consumption.

APPLICATIONS :

MULTI-TEC + B4 10W30 is a universal fuel economy motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. This motor oil is specially developed for those cars that ask for the most recent specifications.

TYPICAL CHARACTERISTICS :

<i>Test</i>	<i>Method</i>	<i>Unit</i>	<i>Average result</i>
SAE-class			10W30
Density at 15°C	D 4052	kg/m ³	869
Viscosity at -25°C	D 5293	cP	5070
Viscosity at 40°C	D 445	cSt	74.90
Viscosity at 100°C	D 445	cSt	11.80
Viscosity index	D 2270		153
Pour point	D 6892	°C	-36
TBN	D 2896	g KOH/kg	8,3
Sulphated ash	D 874	Mass %	1,08

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.