

RACING PLUS 5W50

FULLY SYNTHETIC RACING MOTOR OIL.

RACING PLUS 5W50 is a fully synthetic engine oil of the latest generation, for the lubrication of all high performance engines.

RACING PLUS 5W50 meets the following requirements:

- API SJ, SL/CF
- ACEA A3/B3
- VW 501.01 / 505.00
- BMW LL-98
- Porsche

ADVANTAGES:

- Excellent fluidity at low temperature.
- Very low resistance at start.
- Exceptional viscosity index.
- Very high thermal stability.

APPLICATIONS:

- 4-stroke gasoline engines, multi-valves, turbo.
- 4-stroke passenger car diesel engines, with or without turbo.

TYPICAL CHARACTERISTICS:

<i>Test</i>	<i>Method</i>	<i>Average result</i>
Density at 15°C	D 4052	855 kg / m ³
Viscosity at 40°C	D 445	118 cSt
Viscosity at 100°C	D 445	18 cSt
Viscosity at -30°C	D 5293	5850 cP
Viscosity index	D 2270	172
Pour point	D 6892	-30 °C
TBN	D 2896	9,5 g KOH/kg
Flash point	D 92	235 °C
Sulphated ash	D 874	1,0 mass %

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

