

SYNTH SX 5W40

SYNTH SX 5W40 is a high performance engine oil of the latest generation, specially designed to meet the strict requirements of manufacturers and composed of non-conventional base oils and high quality additives.

SYNTH SX 5W40 meets the following performance criteria:

- API SN/CF
- ACEA A3/B3/B4
- VW 502.00/505.00
- MB 229.3
- Porsche/BMW Longlife-01
- Opel GM-LL-B-25

ADVANTAGES :

A universal, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density @15°C	ASTM D4052	kg/l	0,857
Viscosity @-30°C		mPa.s	6140
Viscosity @40°C	ASTM D7042	mm ² /s	83,80
Viscosity @100°C	ASTM D7042	mm ² /s	14,00
Viscosity Index	ASTM D2270		173
Flash point COC	ASTM D92	°C	223
Pour point	ASTM D97	°C	-39
Total Base Nummer	ASTM D2896	mgKOH/g	9,7
Sulphated Ash	ASTM D874	%	1,22

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

